

Construction

- 6005 T-5 Proprietary Extruded Aluminum Frame & Corners
- Grade 5 Zinc Plated Bolts & Nylock Nuts
- 1" x 2" Rectangle Aluminum Tube Centerbrace
- Dual Locks Provide Deck to Deck Attachment
- 1" x 3/16" 6063T-4 Mill Finish Grated Aluminum Surface

Features:

- Nylock Nuts Eliminate Noise Interference & Feedback from Vibration
- Bolt Construction Frame Allows for Easy Field Repair Instead of Replacement
- Dual Locks are Activated from the Top or Bottom of Decks
- Velcro Allows for Easy Installation of Fabric Skirting or Hard Closure Panels

Performance:

- 200 lbs. per Square Foot Certified Live Load Rating

Locking Mechanism:

- Steel Zinc Plated Chromate Dipped Dual Locks Provide 2,500 lbs. of Tensile Strength

Velcro:

- 3/4" Black Male Velcro Installed in Specially Designed Inset Channel on Extrusion

Weight:

- Approximately 149 lbs. per 4' x 8' Deck

Available Sizes:

- From 12" x 12" up to 4' x 8'

Options:

- Powder Coated or Anodized in a Variety of Colors




Female Dual Lock



Male Dual Lock



Center Brace



Leg Receiver



Corner Extrusion