

**Construction**

**Features:**

- 6005-T5 EXTRUDED Aluminum Frame & Corners
- 1" Thick 9-Ply Marine Grade Plywood
- Grade 5 Zinc Plated Bolts
- #10 Zinc Plated Bolts
- 6 Leg Sockets per 4' x 8' deck
- Certified live weight load of 200 lbs per square foot
- Nylock nuts eliminate vibration and noise interference
- Dual Lock locking system activated from top or bottom of decks
- Center Support Brace

**Weight:**

- Approx. 130-140 Pounds, Varies with surface selection (4' x 8' Stage Deck)

**Surface Options:**

- Non-Skid Quad\*
  - Smooth Haircell Polyvinyl\*
  - Pepper Grey Carpet
  - Black Carpet
  - Clear Plexi
  - Milk Plexi
  - Unfinished Plywood\*
  - Custom Surfaces: Plyron, Diagonal Punch Aluminum Plank, Tongue & Groove and custom carpet.
- All surface options with the exception of the grated aluminum or Diagonal Punch Aluminum Plank are easily removable and can be interchanged to provide versatility to our decks.

\*The Quad or Poly surfaces can be treated to become weather resistant.

\*Unfinished plywood can be finished with stain, clear polyurethane or flame retardant black paint.



Leg Socket



Center Support Brace



Male Dual Lock



Female Dual Lock